

## **Listing of Claims:**

1. (Canceled).
2. (Previously Presented) A universal collar secured to a container used in a dispenser having a keyplate with a keyway that is adapted to receive a complementary shaped collar key associated with an intended container, the universal collar comprising:

a body having a first flange and a second flange, wherein said flanges extend outward and are axially spaced from each other for receiving the keyplate therebetween, wherein said body includes a keyless surface between said first and second flanges such that the universal collar bypasses the keyway of the dispenser, and wherein said flanges are connected on a forward side of the universal collar by a vertically extending rib.
3. (Previously Presented) A universal collar secured to a container used in a dispenser having a keyplate with a keyway that is adapted to receive a complementary shaped collar key associated with an intended container, the universal collar comprising:

a body having a first flange and a second flange, wherein said flanges extend outward and are axially spaced from each other for receiving the keyplate therebetween, wherein said body includes a keyless surface between said first and second flanges such that the universal collar bypasses the keyway of the dispenser, and wherein said at least one of said flanges defines a notch on a rearward side thereof for receiving a projecting portion of the dispenser.
4. (Currently Amended) The universal collar of Claim 3, wherein said notch is centered within said ~~flange~~ flanges on said rearward side.
5. (Previously presented) A universal collar that attaches to a pump and, in turn, a container used in a dispenser having a keyplate, the universal collar comprising:

a body having a first flange and a second flange, wherein said flanges extend outward and are axially spaced from each other for receiving the keyplate therebetween, wherein said body includes a top edge, said top edge defining a locating recess for receipt of a projection on the container, said recess having a base and a pair of upstanding sides, wherein said sides are circumferentially spaced from each other for receipt of the projection therebetween.

6. (Original) The universal collar of Claim 5, wherein one of said sides extends perpendicular to said base and the other of said sides extends obliquely relative to said base.
7. (Original) The universal collar of Claim 5, wherein said top edge extends axially upward relative to said first flange and extends in a circular fashion to circumscribe a portion of the container.
8. (Canceled).
9. (Canceled)
10. (Canceled).
11. (Canceled).